

ENERGY EFFICIENCY

Thermal Transmission Coefficient

U_w from 0,8 (W/m²K)

Please consult typology, dimensions and glazing.

ACCOUSTIC INSULATION

Maximum glazing: **50 mm**

Maximum accoustic insulation: **Rw = 46 dB**

CATEGORIES ACHIEVED AT TEST CENTRE

Protection against atmospheric agents

Air permeability (UNE-EN 12207):

Water tightness (UNE-EN 12208):

Wind resistance (UNE-EN 12210):

Reference test window 1,23 x 1,48 m 1 Sash

Class 4

Class E1650

Class C5

SECTIONS	Frame 80 mm Sash 80 mm
PROFILE THICKNESS	Window 1,9 mm
MAXIMUM DIMENSIONS	Standard solution Width (L) = 1300 mm Height (H) = 2400 mm Cortizo hinges HD hung Width (L) = 1200 mm Height (H) = 3500 mm
MAXIMUM WEIGHT/SASH	160 Kg
FINISHES	Colour powder coating (RAL, mottled, rough...) According to Qualicoat >60 microns Wood effect powder coating According to Qualideco standard Anodized According to Ewwa Euras Standard Class 15 Optionally Class 20 and 25 Optionally bicoloured
HARDWARE	Optionally concealed hinges Optionally security hardware

Please consult maximum dimensions according to types.

EXTRUSION ALLOY

6063 T-5

POLYAMIDE STRIP LENGTH

Polyamide 6,6 reinforced with 25% fiberglass:
45 mm

GASKETS

EPDM triple gasket

FOAMS

Perimeter polyolefin foam in glazing rebate zone

OPENING POSIBILITIES

INWARDS	1 & 2 sashes Side Hung 1 & 2 sashes Turn&tilt Bottom hung
---------	---

